10/789,650

Amendment Dated: January 17, 2008

Reply to Office Action of: July 20, 2007

AMENDMENT TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) A beverage-making apparatus, comprising: a housing,

an electric motor located within the housing,

a torque transmission supported by the housing and receiving input from the electric motor and providing a first output shaft and a second-speed output shaft that rotates at a different speed than the first output shaft,

a crushing module supported by the housing and receiving torque from the first output shaft, and

a blending module receiving torque from the second output shaft comprising a whisk driven by the second-speed output shaft, a vessel into which the whisk depends and a vessel lid fitted to the vessel, the vessel lid comprising a vessel lid upper having a coupling attached to the second-speed output shaft, and a lid lower through which torque is transmitted from the coupling to the whisk.

- 2. (Original) The apparatus of Claim 1 wherein the second-speed output shaft rotates at a different speed and in a different direction than the first output shaft.
- 3. (Original) The apparatus of Claim 1 wherein the crushing module comprises a contoured crushing disk that bears down upon a beverage ingredient, and a blade against which the beverage ingredient is crushed by the crushing disk.
- 4. (Original) The apparatus of Claim 3 wherein the crushing disk is attached to the first output shaft.

10/789,650

Amendment Dated:

January 17, 2008

Reply to Office Action of:

July 20, 2007

5. (Canceled)

6. (Currently amended) The apparatus of Claim [[5]] 1 further comprising a second whisk driven by the first output shaft, and wherein the second-speed output shaft rotates at a different speed and in a different direction than the

first output shaft.

7. (Original) The apparatus of Claim 1 wherein the torque transmission

comprises a gearbox.

8. (Original) The apparatus of Claim 6 wherein the first and second output

shafts are co-linear and extend from opposite sides of the gearbox.

9. (Original) The apparatus of Claim 1 wherein the housing comprises a

base upon which the vessel is supported.

10. (Original) The apparatus of Claim 1 wherein the crushing module

comprises a hinged lid.

11. (Currently amended) The apparatus of Claim 1 further comprising a

blade against which the beverage ingredient is crushed by the crushing disk

and a funnel depending from the blade toward the blending module.

12. (Canceled)

13. (Currently amended) A beverage-making apparatus, comprising:

a housing,

an electric motor located within the housing,

MCHK/163/US

- 3 -

10/789,650

Amendment Dated:

January 17, 2008

Reply to Office Action of:

July 20, 2007

a torque transmission supported by the housing and receiving input from the electric motor and providing an output,

a crushing module supported by the housing and receiving torque from the output, the crushing module comprising a contoured crushing disk that bears down upon a beverage ingredient having a boss, an outer ring coaxial with the boss and two diametrically opposed contoured paddles positioned between the boss and the outer ring for bearing down upon the beverage ingredient, and a blade against which the beverage ingredient is crushed by the crushing disk, and

a blending module receiving torque from the output, and positioned to receive the beverage ingredient crushed by the crushing disk.

14. (Canceled)

- 15. (Currently amended) The apparatus of Claim [[14]] 13 wherein the boss includes a bore having splines for coupling with the output.
- 16. (Currently amended) The apparatus of Claim [[14]] 13 wherein the paddles have a pitch that forces beverage ingredient at a front of the paddles against the blade.

17-20. (Canceled)

21. (Original) A beverage-making apparatus, comprising:

a housing,

an electric motor located within the housing,

a torque transmission supported by the housing and receiving input from the electric motor and providing an output,

a crushing module supported by the housing and receiving torque from the output, the crushing module comprising a contoured crushing disk that bears

10/789,650

Amendment Dated:

January 17, 2008

Reply to Office Action of:

July 20, 2007

down upon a beverage ingredient, and a blade against which the beverage ingredient is crushed by the crushing disk, and

a blending module positioned to receive the beverage ingredient crushed by the crushing disk, the blending module comprising a blending housing having a coupling for receiving torque from the output, a second torque transmission supported by the blending housing and receiving input from the coupling and providing a first output shaft and a second-speed output shaft that rotates at a different speed than the first output shaft, the first output shaft being positioned within the second output shaft, and a first whisk receiving torque from the first output shaft and a second whisk receiving torque from the second output shaft.

- 22. (Original) The apparatus of Claim 21 wherein the second output shaft rotates in a different direct to the first output shaft.
- 23. (New) A beverage-making apparatus, comprising:

a housing,

an electric motor located within the housing,

a torque transmission supported by the housing and receiving input from the electric motor and providing a first output shaft and a second-speed output shaft that rotates at a different speed than the first output shaft,

a crushing module supported by the housing and receiving torque from the first output shaft, and

a blending module receiving torque from the second output shaft, the blending module comprising a first whisk driven by the second-speed output shaft, a second whisk driven by the first output shaft and a vessel into which the whisks depend.

10/789,650

Amendment Dated:

January 17, 2008

Reply to Office Action of:

July 20, 2007

24. (New) The apparatus of Claim 23 wherein the second-speed output shaft rotates at a different speed and in a different direction than the first output shaft.

- 25. (New) The apparatus of Claim 23 wherein the crushing module comprising a contoured crushing disk having a boss, an outer ring coaxial with the boss and two diametrically opposed contoured paddles positioned between the boss and the outer ring for bearing down upon the beverage ingredient, and a blade against which the beverage ingredient is crushed by the crushing disk.
- 26. (New) The apparatus of Claim 23 wherein the blending module further comprises a vessel lid comprising a vessel lid upper having a coupling attached to the second-speed output shaft, and a lid lower through which torque is transmitted from the coupling to the whisk.
- 27. (New) The apparatus of Claim 23 wherein the first and second output shafts are co-linear and extend from opposite sides of the gearbox.
- 28. (New) A beverage-making apparatus, comprising:
 - a housing,
 - an electric motor located within the housing,
- a torque transmission supported by the housing and receiving input from the electric motor and providing a first output shaft and a second-speed output shaft that rotates at a different speed than the first output shaft,
- a crushing module supported by the housing and comprising a contoured crushing disk driven by the first output shaft and having a boss, an outer ring coaxial with the boss and two diametrically opposed contoured paddles positioned between the boss and the outer ring for bearing down upon the

10/789,650

Amendment Dated:

January 17, 2008

Reply to Office Action of:

July 20, 2007

beverage ingredient, and a blade against which the beverage ingredient is crushed by the crushing disk, and

a blending module comprising a whisk driven by the second-speed output shaft a vessel into which the whisk depends and a vessel lid fitted to the vessel, the vessel lid comprising a vessel lid upper having a coupling attached to the second-speed output shaft, and a lid lower through which torque is transmitted from the coupling to the whisk.

29. (New) The apparatus of Claim 28 further comprising a second whisk driven by the first output shaft, and wherein the second-speed output shaft rotates at a different speed and in a different direction than the first output shaft.